

call Kevin on 07891593870  
[www.aquatico.co.uk](http://www.aquatico.co.uk) or email: [roanfish@blueyonder.co.uk](mailto:roanfish@blueyonder.co.uk)



### Accessory



### 50 HZ

Models		Power kW		kW absorbed		Capacity l/min	r.p.m.	Nominal power HP	Weight Kg	Motor cable length m
Single - phase 230 V - 50 Hz	Three - phase 400 V - 50 Hz	Single - phase 230 V - 50 Hz	Three - phase 400 V - 50 Hz	Single - phase 230 V - 50 Hz	Three - phase 400 V - 50 Hz					
<b>SPLASH 0,5/2001M</b>	<b>SPLASH 0,5/2001T</b>	0.37	0.37	0.6	0.6	2000	1400	0.5	24	20
<b>SPLASH 1/2001M</b>	<b>SPLASH 1/2001T</b>	0.75	0.75	1.2	1.2	3200	1400	1	25	20
<b>SPLASH 1/2008M</b>	<b>SPLASH 1/2008T</b>	1.3	1.3	1.7	1.7	3100	2800	1.5	25	20

Other voltages and frequency available on request. Description, technical data and features are not binding. The company reserves the right to carry out any modification without notice.

- Light weight easy to handle. Simply one person can carry and install the unit.
- Corrosion proof. Suitable for use in salt water or fresh water.
- Easy and low cost maintenance. Can be serviced by the user.
- Double propeller high flow capacity performance on 1400 rpm models.
- Single propeller for fountain like water stream on 2800 rpm models.
- CE certified.
- Energy efficient for successful water quality management with no bottom turbulence.

call Kevin on 07891593870  
[www.aquatico.co.uk](http://www.aquatico.co.uk) or email: [roanfish@blueyonder.co.uk](mailto:roanfish@blueyonder.co.uk)